



## Controlled Dehumidification

5931 Ford Court Brighton, MI 48116 • 810.229.7900

Fax: 810.229.7908 • sales@ctrdh.com • ctrdh.com

### MS-5000/4000-ARID-Dry Desiccant Dehumidifier

<u>Model</u>	<u>CFM</u>	<u>Fuel Type</u>	<u>Length</u>	<u>Width</u>	<u>Height</u>	<u>Weight</u>
MS 5000/4000	5,000/4,000*	Electric	98" **	46"	77"***	1,950 lbs
MS 5000/4000	5,000/4,000*	Gas	98" **	46"	77"***	1,975 lbs

<u>Model</u>	<u>Moisture Removal Lbs/Hr 80°/60% RH</u>	<u>Moisture Removal Gallons/Day 80°/60% RH</u>	<u>Moisture Removal Lbs/Hr 55°/80% RH</u>	<u>Moisture Removal Gallons/Day 55°/80% RH</u>	<u>Moisture Removal Lbs/Hr 40°/80% RH</u>	<u>Moisture Removal Gallons/Day 40°/80% RH</u>
MS 5000/4000-E	102	295	87	251	56	161
MS 5000/4000-G	102	295	87	251	56	161

<u>Model</u>	<u>Pipe Size</u>	<u>LP Inlet Pressure</u>	<u>Natural Gas Inlet Pressure</u>	<u>Electric Reactivation FLA Load 460/3/60</u>	<u>CFH Gas Max Usage NG</u>	<u>Gallon/HR Max Usage LP</u>
MS 5000/4000-G	N/A	N/A	N/A	112	N/A	N/A
MS 5000/4000-E	3/4"	7-14" w.c.	7-14" w.c.	N/A	359	3.9



#### Available Accessories

- Lifting/stacking cage
- Heavy duty casters and brackets
- Remote Humidistat
- Trailer Mounting
- 18" or 20" Round Connections
- Ductwork and layflat

- \*5000 cfm @ 0" of W.C 4000CFM @ 4.25" of W.C.
- \*\* Optional Casters and brackets -add 12" to length and 8" to heights
- \*\*\*Optional Lifting/stacking cage –add 6" to height and 323lbs